

Delta Pack

Versatile and streamlined kit

Part number

DP10UL01UN12/23

The Delta Pack, which includes an Si-10 pump, is a complete kit intended for wall-mounted air conditioning units. The piston technology of the Si-10 is specifically designed for removing condensate from air conditioning systems. With the insulation foam and anti-vibration bracket, the pump's operating sound level will remain very silent (22dBA) whatever the amount of condensate. The pack can be mounted on either side of the unit.



- ⊕ Modern and compact design
- ⊕ Silent operation: 22 dBA at full power
- ⊕ Easy installation, on any surface
- ⊕ Easy maintenance, with lockable plug-in power cable
- ⊕ Proven reliability

Technical details

Max flow rate	5 gph
Max discharge head	33 ft
Max pressure	46 ft
Insulation class	Double insulation
Mains supply	230V ~ 50/60Hz ~ 14W
Operation conditions	100% Marche continue
Protection	IPX4
Weight	1,000.50 lb
Color	RAL 9010
Master pack quantity	10
Safety switch	NC 8A resistif - 250V

Detection Bloc de détection

Thermal protection 115°C (redémarrage automatique)

Detection levels

Pump sound levels

ON	3 5/32"	at 3,3ft or 1m according to EN ISO3744 (dBA)	none 22
OFF	3 5/32"	at 3,3ft or 1m in application (dBA)	<= 25
SAFETY	3 5/32"		

Kit contents

Si-10 piston pump, with integrated float detection unit
Clear PVC tube (6mm internal diameter - length 1m - foam-insulated over 800mm), fitted with a Drain Safe Device pre-mounted)
1,5 m lockable plug-in power cable, with 2 power wires and 2 safety contact wires
Duct 30 "
2 part elbow (base + cover)
Ceiling duct cover
Elbow/Duct gasket
Rubber elbow/split gasket
Rubber tube (internal diameter 15 mm - connects to split) 20 "
Vent pipe
6 screws and plugs for fixing duct and elbow
2 pipe clamps

Pump technology

Mini condensate removal pump

Installation

Next to unit

Application

Air conditioning

Safety standards

CE
EAC

Ro
HS
and
WE
EE
dire
ctiv
es

Com
plia
nt



Source URL: <https://sauermann.us/en-US/product/pump/delta-pack>