

Si-10: Compact Monobloc Mini Condensate Removal Pump

Next to the Unit

Part number
SI10UL02UN23

Integrated detection unit for install in tight spaces.

- + Compact monobloc construction
- + Integrated detection unit
- + Anti-vibration mounting bracket
- + Quiet operation



Technical details

Max flow rate	5 gph
Max discharge head	33 ft
Max pressure	46 ft
Insulation class	Double insulation
Mains supply	230V: (SI10UL01UN23)
Operation conditions	70%: 3s ON - 1s OFF
Weight	0.86 lb
Master pack quantity	25
Safety switch	NC 8A resistive - 250 V

Detection Integrated detection unit

Thermal protection 240 deg. F (auto-reset)

Pump dimensions

Detection levels

	Length	Width	Height		
Pump	2 5/8"	1 3/4"	3"	ON	23/32"
				OFF	15/32"

	Length	Width	Height		
Packaging	4 13/32"	3 19/32"	3 19/32"	SAFETY	13/16"

Pump sound levels

at 3,3ft or 1m according to EN ISO3744 (dBA)

<= 23

Kit contents

Si-10 piston pump, with integrated float detection unit
 Anti-vibration mounting bracket
 Power Cable, 5' (2 power wires, 2 safety wires)
 90 Deg Rubber Elbow, 19/32" i.d. x L 2 1/3"
 Vent Tube, 5/32" i.d. x L 2 15/16"

Pump technology

Mini condensate removal pump

Installation

Next to unit
 Wall mounted

Application

Air conditioning

Safety standards

UL/CSA by Intertek



Source URL: <https://sauermann.us/en-US/product/pump/si-10-compact-monobloc-mini-condensate-removal-pump>