

# Si-10: Compact Monobloc Mini Condensate Removal Pump

## Next to the Unit

**Part number**  
SI10UL02UN23

Integrated detection unit for install in tight spaces.

- + Compact monobloc construction
- + Integrated detection unit
- + Anti-vibration mounting bracket
- + Quiet operation



### Technical details

Max flow rate	5 gph
Max discharge head	33 ft
Max pressure	46 ft
Insulation class	Double insulation
Mains supply	230V: (SI10UL01UN23)
Operation conditions	70%: 3s ON - 1s OFF
Weight	0.86 lb
Master pack quantity	25
Safety switch	NC 8A resistive - 250 V

Detection Integrated detection unit

Thermal protection 240 deg. F (auto-reset)

#### Pump dimensions

#### Detection levels

	Length	Width	Height		
Pump	2 5/8"	1 3/4"	3"	ON	23/32"
				OFF	15/32"

	<b>Length</b>	<b>Width</b>	<b>Height</b>		
Packaging	<b>4 13/32"</b>	<b>3 19/32"</b>	<b>3 19/32"</b>	SAFETY	<b>13/16"</b>

#### Pump sound levels

at 3,3ft or 1m according to EN ISO3744 (dBA)

**<= 23**

#### Kit contents

Si-10 piston pump, with integrated float detection unit  
 Anti-vibration mounting bracket  
 Power Cable, 5' (2 power wires, 2 safety wires)  
 90 Deg Rubber Elbow, 19/32" i.d. x L 2 1/3"  
 Vent Tube, 5/32" i.d. x L 2 15/16"

#### Pump technology

Mini condensate removal pump

#### Installation

Next to unit  
 Wall mounted

#### Application

Air conditioning

#### Safety standards

UL/CSA by Intertek



**Source URL:** <https://sauermann.us/en-US/product/pump/si-10-compact-monobloc-mini-condensate-removal-pump>